

EOI FOR SUPPLY OF AGRICULTURE & ALLIED SECTOR, AGRO INDUSTRY AND FOOD PROCESSING RELATED EQUIPMENT /MACHINERY / MATERIALS AND EQUIPMENT AND MACHINERY FOR LAND DEVELOPMENT ACTIVITIES DURING THE YEAR 2023-24.

Last date for submission of EOI schedule	:	17-11-2023 upto 2.00 PM
Date of opening of Technical Bid	:	17-11-2023 at 2.30 PM



### ANDHRA PRADESH STATE AGRO INDUSTRIES DEVELOPMENT CORPORATION LIMITED

G1, G2, 101, Prime Hill Crest, Vaddeswaram, Guntur District Email: gmapagros@gmail.com, web site: www.apagros.org

#### A.P.S. AGRO INDUSTRIES DEVELOPMENT CORPORATION LTD.



Regd.Office:G1, G2, 101, Prime Hill Crest, Vaddeswaram, Guntur District website: www.apagros.org. E.Mail: gmapagros@gmail.com

EOI FOR SUPPLY OF AGRICULTURE & ALLIED SECTOR, AGRO INDUSTRY AND FOOD PROCESSING RELATED EQUIPMENT /MACHINERY /MATERIALS AND EQUIPMENT AND MACHINERY FOR LAND DEVELOPMENT ACTIVITIES DURING THE YEAR 2023-24.

Ref: Notification No. APSAIDCL/GS/2023-24/005, Dt.27-10-2023.

\*\*\*\*\*

#### A. <u>Preamble:</u>

Technical Bids & Price Quotations are invited from manufacturers for supply of following Agriculture & Allied Sector, Agro Industry and Food Processing related Equipment/Machinery/Materials and equipment and machinery for Land Development Activities during the year 2023-24 in the State of Andhra Pradesh.

Description	Cost of EOI schedule	Sale of EOI Schedules From – to	Last date for submission	Date of openingof Technical bids
Supply of Agriculture & Allied Sector, Agro Industry and Food Processing related Equipment/Machinery/M aterials and equipment and machinery for Land Development Activities during the year 2023-24 in the State of Andhra Pradesh	Rs.10,000	30-10-2023 to 17-11-2023 up to 12.30 PM	17-11-2023 up to 2.00 PM	17-11-2023 at 2.30 PM

Application schedule can be downloaded from our website: <a href="www.apagros.org">www.apagros.org</a>. DD of Rs.10,000/- in favour of APSAIDC Ltd., payable at Vijayawada shall be enclosed for each schedule. The last date for submission of filled-in Applications at our Registered Office on 17-11-2023 up to 02-00 PM.

#### Table 1:

#### **List of Items**

Items	Items NoI: Farm Machinery & Equipment			
1	Land Preparatory Equipments			
2	Secondary Land Preparatory Equipments			
3	Sowing & Planting Equipments			
4	PP Equipments			
5	Harvesting Equipments			
6	Post Harvesting Equipments			
7	Power Tillers / Brush Cutters			

9	Self Propelled Tree Maintenance Platforms				
10	Crop Residue Management Equipments				
11	ISI Marked HDPE Tarpaulins and Multi Layard Cross Laminated Sheets (with				
11					
12	size & GSM wise quote) Tractors (All Models)				
13	· · · · · · · · · · · · · · · · · · ·				
	Oil Engines & Pump Sets / Electrical Motors				
14 15	Pheromone Traps + Lures(with item wise quote)  Solar Pest Traps				
	1				
16 17	Yellow Sticky Plates (with item wise quote)				
	Water Carrying Pipes (PVC/HDPE/Sprinklers)				
18	200 Liters Drum without LID (new HDPE)				
19	100 Liters Drum without LID (new HDPE)				
20	Any other Items required by Agriculture Department				
	No-II: Equipment for Horticulture Department Crops				
1	Plastic Crates  Conden Treels				
2	Garden Tools  Polishors (for Turmonia)				
3	Polishers (for Turmeric)				
4	Boilers (for Turmeric)				
5	Aluminum Ladders (Uni-pole) (for coffee)				
6	Drip irrigation and Sprinklers				
7 8	Aluminum Ladders (Bi-pole) (for coffee)				
Items	Any other Items required by Horticulture Department				
1	tments/Government organizations  Compactors				
2	Vehicle mounted Sky Lifters/Ladders				
3	Back Hoe Loader				
4	3 wheel/4 wheel Autos				
5	Hydraulic Tippers				
6	Vehicle mounted open Nala De-silting machines				
7	Vehicle mounted Sewer suction cum jetting machines				
8	Sanitary tools, Garden tools				
9	Compactor Bins				
10	Canal cleaning machines				
11	Sand cleaning machines				
12	Garbage picking machines				
13	Post hole Diggers				
14	Skid-Steer Loaders				
15					
	venicle mounted Sweeping machines				
1.0	Vehicle mounted Sweeping machines Plastic Bins				
16 17	Plastic Bins				
17	Plastic Bins Hand Operated Fogging machines & Vehicle mounted fogging machines				
17 18	Plastic Bins Hand Operated Fogging machines & Vehicle mounted fogging machines Mist blowing machines (for control of air pollution)				
17	Plastic Bins Hand Operated Fogging machines & Vehicle mounted fogging machines				
17 18 19	Plastic Bins Hand Operated Fogging machines & Vehicle mounted fogging machines Mist blowing machines (for control of air pollution) Composting machines				
17 18 19 20	Plastic Bins Hand Operated Fogging machines & Vehicle mounted fogging machines Mist blowing machines (for control of air pollution) Composting machines Excavators Chain mounted Dozer				
17 18 19 20 21 22	Plastic Bins Hand Operated Fogging machines & Vehicle mounted fogging machines Mist blowing machines (for control of air pollution) Composting machines Excavators				
17 18 19 20 21 22	Plastic Bins Hand Operated Fogging machines & Vehicle mounted fogging machines Mist blowing machines (for control of air pollution) Composting machines Excavators Chain mounted Dozer Any other Items required by Municipalities				
17 18 19 20 21 22 <b>Items</b> 1	Plastic Bins Hand Operated Fogging machines & Vehicle mounted fogging machines Mist blowing machines (for control of air pollution) Composting machines Excavators Chain mounted Dozer Any other Items required by Municipalities No-IV: Equipment for Food Processing Industry				

3	Processing Machinery					
4	Seamers & Cappers					
5	Conveyers / Emulsifiers / Agitators / Boilers / Freezers					
6	Pellet making Machinery					
7	Any Other Items required for Food Processing Industry					
Items 1	ms No-V: Equipment for Animal Husbandry Department & Dairy					
1	E.C.G for Dogs					
2	Endoscopy for Small Animals					
3	Endo-tracheal Tube with Cuff Disposable					
4	Gloves Obstetrical					
5	Vital Signs Monitor					
6	Otoscope with light source plain					
7	Small Animal Anesthetic Machine with Isoflurane Vapourizer and Sevoflurane					
8	ST-200 CL Electrolyte Analyzer					
9	Endoscopic Monitor					
10	Veterinary Orthopedic Pinning and Plating Kit					
11	Veterinary Blood pressure Monitor					
12	Ophthalmic Ultrasound Scanner A scan					
13	Cardiac Defibrillator with ECG					
14	Absolute Alcohol					
15	California Mastitis Reagent					
16	Gel Green					
17	Glycerine					
18	Iodine Tr. IP					
19	Petroleum spirit					
20	Polyclonal Rabbit Anti Cow -HRPO Conjugate					
21 22	Polyclonal Rabbit Anti Guinea Pig Ig G -HRPO Conjugate					
	Fire extinguisher					
23	Gas cylinder with regulator and rubber tube Reverse Osmosis System (Big)					
25	Milli-Q ultrapure type I water purification system					
26	Hand held smart strip based somatic cell counter					
27	Sub-cell GT cell					
28	Tab Digital Microscope					
29	UPS with 1KV Battery backup					
30	Refrigerator					
31	Conical flasks-100 ml with screw cap					
32	Conical flasks-1000 ml with screw cap					
33	Conical flasks-2000 ml with screw cap					
34	Conical flasks-250 ml with screw cap					
35	Conical flasks-50 ml					
36	Micrometer slides					
37	Bio chemical kits for fully automatic biochemical analyzer for serum albumin					
38	Biochemical kit for fully automatic biochemical analyzer for Alkaline					
	Phosphatase					
39	Biochemical kit for for fully automatic biochemical analyzer for serum ALT					
40	Biochemical kit for fully automatic biochemical analyzer for serum AST					

41	Biochemical kit for serum Magnesium - For fully automatic analyzer (idexx)
42	Biochemical kit for serum Potassium -For fully automatic analyzer (idexx)
43	Biochemical kit for fully automatic analyzer for serum Total Proteins
44	Biochemical kit for fully automatic analyzer serum Urea Nitrogen
45	Blood - TUBES QBCW/STRIPE (IDEXX)
46	Controls for Semi Automatic Hematology Analyzer
47	ELISA Kit- Malignant Catarrhal fever Antigen detection kit
48	ELISA Kit-Malignant Catarrhal fever Antibody detection kit
49	FAMACHA Cards
50	Hand Disinfectant Gel
51	IDEXX E-Z prep Pipetter
52	IDEXX vet tubes
53	IDEXX VetTrol Control
54	Kits for Semi Automatic Biochemical analyzer
55	Kits-Blood - BOVINE Hematology sample prep kit for Idexx analyzer
56	Mac master egg counting Chamber (glass)
57	Microscopic slide tray
58	Paraffin -wax
59	Poly propylene vials
60	Sample cups with cap for clinical chemistry analyzer
61	Specimen Container 250ml
62	Strip cup for mastitis test
63	U-V Lamps with cabinets
64	Vacutainer with K2 EDTA
65	Wall mounted SOP display boards (pads)
66	Whatman filter paper
67	Whatman filter paper
68	Whatman filter paper no 40
69	Brucella anti body rapid detection test kit
70	Ammonium sulphate solution
71	Blood Agar readymade plates
72	Liquor ammonia
73	Lugols Iodine
74	Magnesium sulphate
75	RG stain
76	Sodium Nitrite
77	Uristix
78	Centrifuge tubes
79	Watch glass
80	Immersion Oil-Type
81	Leak Proof Containers
82	Ammonium Hydroxide
83	Sodium/ Potassium Hydroxide flakes
84	Microscope Slides
85	Microscopic slides-Frosted
86	Brush Cutters

87	Tractor Mounted Single Row forage Harvester cum Chaffer
88	Vermicompost Unit
89	Mawa Making unit
90	Ghee Making unit
91	Butter chilling unit
92	Urine Distillery Unit
93	Cow dung log machine
94	Panchagavyam unit
95	Jeevamrutham Unit
96	Agarbathi Making unit
97	Biochemical Analyzer
98	X-Ray Unit Digital
99	Large Animal Trolley cum Operation table
100	Ultraviolet lights
101	Movable Trolley
102	LCD Projector with screen
103	White Board with stand
104	Digital X-Ray Machine
105	Endoscopy for small animals
106	Large animal operation table with hydraulic system
107	Boyles apparatus
108	Movable Large Animal Surgical Table
109	Morbros make General surgery semi electric OT Table
110	LARGE ANIMALMULTIPLE USE TROLLEY - For Transportation and
110	surgery – custom made Sizes: length 7/8 feet, width: 5/6 feet and height 2 feet with or without heavy duty wheels
111	PZ make AD X model 500MAX Ray Machine with DR System
112	Largngo Scope
113	Spay hook
114	Woods Lamp
115	Eye Speculum
116	Vital Sign Monitor
117	Inhalation anesthetic Machine with automatic ventilation support along with
117	isoflurane vaporizer
118	United Surgical Model make double dome Surgical operating LED light Model
	80D
119	ECG Machine
120	Doppler BP Monitor
121	Vet Endoscopy
122	Infrared Thermometer
123	LED pocket Otoscope
124	Binocular Indirect Ophthalmoscopes
125	Endotracheal tube size 16 Endotracheal tube size 18
126 127	Endotracheal tube size 18 Endotracheal tube size 20
141	Endotrached tube size 20

128	Endotracheal tube size 22
129	Metal Detector
130	Autoclave with 4 Dressing Drums, 2 drums can be fitted with autoclave
131	Backhaus towel clamps
132	Large animal anesthetic machine
133	wireless oscillating ortho saw
134	Rubber mats
135	Wire Tensioner
136	Hammer
137	LCP PLATE - 2.7mm - 6H
138	LCP PLATE - 2.7mm - 8H
139	LCP PLATE - 2.7mm - 10H
140	LCP SCREW - 2.7mm - 10mm
141	LCP SCREW - 2.7mm - 12mm
142	LCP SCREW - 2.7mm - 14mm
143	LCP SCREW - 2.7mm - 16mm
144	LCP SCREW - 2.7mm - 18mm
145	LCP SCREW - 2.7mm - 20mm
146	LCP PLATE - 3.5mm - 8H
147	LCP PLATE - 3.5mm - 10H
148	LCP PLATE - 3.5mm - 12H
149 150	LCP SCREW - 3.5mm - 14mm LCP SCREW - 3.5mm - 16mm
151	LCP SCREW - 3.5mm - 18mm
152	LCP SCREW - 3.5mm - 20mm
153	LCP SCREW - 3.5mm - 22mm
154	LCP SCREW - 3.5mm - 24mm
155	LCP SCREW - 3.5mm - 26mm
156	LCP SCREW - 3.5mm - 28mm
157	LCP SCREW - 3.5mm - 30mm
158	Nebulizer
159	X-ray-illuminator
160	Travis
161	Auto clave
162	Surgical bins
163	Autoclave
164	Thermo cautery
165	Large animal surgical Kit
166	Small animal surgical kit
167	Pulse Oximeter
168	Operation table for small ruminants
169	Hydraulic operation table for large animals
170	Surgical Oscillating saw
171	Suturing material
172	Air Conditioner in Operation theatre
173	Inhalation Anesthetics Machine

174	Surgical light Head
175	Vital signs Monitor
176	Otoscope
177	Electronic Stethoscope
178	ECG machine
179	Microscope with Monitor
180	Vein finder
181	Gastro scope
182	Vet scope
183	Electric thawing Units
184	Anesthetics
185	Drapes
186	Surgical needles
187	Mouth Gags
188	Trocar and cannula( large & small)
189	Rumen Puncture Needle
190	Obstetrical Hooks
191	Obstetrical Lubricants
192	Disposable Plastic polygraphs for Surgeries
193	Electrical fans
194	LED tube lights
195	LPG gas and stove with regulator
196	Electrical shaver
197	Manual Shavers
198	Towel clips
199	liquid soap
200	PH papers
201	Glass slides
202	Fore Head Thermometers
203	Case sheets
204	Registers
205	Infrared Bulb
206	Ketamine
207	Table for ultra sound machine
208	Lead Aprons
209	Lead Glues
210	Chemicals for Developer, Fixer Rinser
211	Tanks for holding chemicals for development of film
212	Safe Light
213	Normal Tube Light
214	Films (8X10, 10,12, 12X15)
215	Clips
216	Existing fan for dark room
217	Saline stands

218	Gaseous anesthesia with isoflurane vaporizer
219	DIGITAL X-RAY UNIT
220	Orthopedic kit
221	Ultrasound latest version
222	Autoclave tubular
223	Surgical Suction machine for large animals
224	Large Animal Sling(lifting system for recumbent /downer animal
225	Surgical equipments (arteries, tissues, scissors, B.P.handles, Rumenotomy set, Retractors, suture material, stools revolving et., for Large animal & Small animal surgeries)
226	Veterinary ECG machine
227	Heavy duty trolley (1-ton capacity) for transportation of recumbent animal from ambulance to the ward
228	Thygesen embryortome set with wire saw
229	Hydraulic Surgical table for large animal (1 ton capacity)
230	Godrej Steel Almirah
231	ECG
232	Boyles Apparatus
233	Electric Thermo Cautery
234	Magnetic Loup
235	Orthopedic Equipment
236	AC
237	Saline stands
238	Medicine Storage Cabinet (Steel Shelve)
239	Saline Stand
240	Small animal Operation table
241	Iron Racks
242	Electrical Shavers
243	Thermometers
244	UV Lamp
245	Small animal OT Table
246	Shadow less light for surgery (Operations)
247	Digital X-ray machine
248	Portable Digital X Ray Machine
249	Portable digital X-Ray Machine
250	Needle Holders

# EOI Schedules & Price Quotes are invited for empanelment of supply of above equipments.

#### B. <u>ELIGIBLE CONDITIONS FOR MANUFACTURER(S)</u>:

- 1. The applicant shall be Original Manufacturers of the items in Table-1.
- 2. The applicant shall submit original firm Registration Certificate.

- 3. The applicant shall be Manufacturers having Certificate Part II or 05 years of completed experience with workshop license for manufacturing as specified in the schedule for supply of different types of equipments.
- 4. The Manufacturer shall have minimum of 05 years of experience in supply of machinery/equipment to any Government Agencies. The certificates shall be submitted
- 5. The Manufacturer shall submit recent power tariff bill of the manufacturing unit of last year active unit.
- 6. The Manufacturer shall submit the labour certificate.
- 7. The Manufacturer shall submit the recent GST invoices of last 06 months anywhere in India.
- 8. The Manufacturer(s) shall have a full fledged manufacturing unit with sufficient personnel for manufacturing of above equipments as per the prescribed specifications.
- 9. The Manufacturer(s) shall have full-fledged distribution/service network in Andhra Pradesh to attend the post sales services and also communicate the details of service dealers in AP.
- 10. The Manufacturers shall have GST, Registration and PAN/TAN/TIN number and firms regularly furnishing information to GST Authorities.
- 11. The Manufacturer shall produce Commercial Test Reports obtained from Farm Machinery Training Testing Institutes (FMTTI)/from ICAR/State Agricultural University Testing Centres approved by GOI for the Farm Machinery & Equipment/ Farm Machinery Testing Center (FMTC) Report/CIPET Report/Any Government organizations & Government Institutions.
- 12. The Manufacturer shall produce ISO/ISI Certificate of the Manufacturer wherever applicable.

<u>Note:</u> The original Manufacturing Company or any authorized person (only one per company) shall only participated in the EOI.

#### C. INSTRUCTIONS FOR SUBMISSION OF EOI SCHEDULE:

- 1. The Manufacturer(s) shall submit EOI Schedule with all documents indicated in Annexure-II in a separate sealed cover duly superscribing EOI Schedule for as per Items Table and Price Quote as per Annexure-III in a separate sealed cover duly superscribing "Price Quote for above equipments" with name and address of the Manufacturer.
- 2. **Financial Bid:** The cost for the quoted equipments should be furnished in Annexure-III.
- 3. The Manufacturer shall submit their application on or before 17-11-2023 at 2.00 PM duly enclosing demand draft of Rs.10,000/- towards non refundable application cost.

Application without DD will be rejected. The eligible manufacturer after empanelment shall deposit **Rs.1,00,000/-** (**One Lakh**) as Performance Guarantee Deposit at the time of submission of Agreement. The DD shall be drawn in favour of APSAIDC Ltd., payable at Vijayawada. The deposit amount shall be refunded without interest as per the request of the successor bidder after completion of warranty period and which will not be refunded within one year.

- 4. The Manufacturer(s) shall submit duly notarized declaration along with EOI, as per the proforma furnished under Annexure-IV on Rs.100/- Non-Judicial stamp paper.
- 5. The authorized person representing the Manufacturers/Directors/Senior employee who can take decisions on behalf of the company) shall invariably attach authorization letter obtained from the competent authority as per rules of the company, to sign and to participate in the empanelment process.
- 6. The price quotations of the manufacturers whose application is technically qualified will only be opened and after opening of the price list, if it is found that the rates quoted are high and are not acceptable, the Technical Committee shall have the right to go for negotiations.
- 7. The proof of attested copies of the documents regarding the status of the manufacturing company should be attached to the Application
- 8. Only representative from Manufacturers with the authorization letter and valid identity is allowed to participate in the Empanelment Process and the company intending to apply should ensure the same.
- 9. The rates quoted in the price list offered by the Manufacturers should valid up to One year from the date of the Agreement. The rates quoted under this EOI in no case shall be more than the prevailing lowest comprehensive dealer price in the market period.

#### D. GENERAL TERMS AND CONDITIONS:

- 1. The Expression of Interest (EOI) applications can be downloaded from <a href="https://www.apagros.org">www.apagros.org</a>.
- 2. The Manufacturer(s) have to quote the prices only as per the technical specifications of their products.
- 3. Negotiations will be held by the State Level Technical Committee at the address indicated in the data sheet.
- 4. The agreement period will be up to one year from the date of signing the agreement. No Escalation charges will be paid for supply of equipment during the agreement period. Failure to supply the equipment due to price variation will attract blacklisting of the firm and shall not be allowed to participate in the EOI process called by any Government Department in Andhra Pradesh for minimum of 03 years under any schemes or in any project.
- 5. The supplies made shall be invoiced on GST invoice with serial No. of Invoice printed on it. No invoice other than Tax invoice will be accepted. GST applicable, if any, shall be clearly mentioned in the Tax invoice.

- The manufacturers participating in the EOI should indicate the details of dealers in the EOI Schedule prescribed. The name of the firm once included in the approved list will not be deleted up to the end of the financial year unless felt by the APSAIDCL.
- 7. The approved firms shall supply the ordered equipment as per terms and conditions within the stipulated time of 21 days indicated in the purchase order placed from time to time to the beneficiary at end customer point and obtain acknowledgement from the beneficiary on the day of delivery.
- 8. The equipment supplied must be covered with warranty for one year from the date of supply against any defective manufacture / workmanship etc., at suppliers own cost. Repairs / Replacements / servicing shall be attended at customer's place during the warranty period at free of cost within 07 days from date of intimation. They shall also ensure that all the components shall be made available through dealers network at least for a period of three years from the date of supply of the unit on payment basis.
- 9. If the supplying firms fail to supply the equipment within the scheduled time i.e.21 days from the date of receipt of purchase order, the action will be initiated as per procedure.
- 10. Liquidated damages will be levied at the rate of 0.5% of the total value of work per week up to a maximum of 5% in case of default in the supply of equipment as per schedule.
- 11. The supplier has to show the demonstration of the equipment to the party, at the time of supply. The firm has to educate the concerned beneficiaries on do's and don'ts of operation of equipment.
- 12. The acknowledgement (Proof of Delivery) and other required documents for the equipment delivered should be signed by the beneficiary and countersigned by the concerned officials of end customer point
- 13. The transportation loading, un-loading charges and demonstration expenses should be borne by the supplier only (transits insurance).
- 14. The manufacturer shall provide detailed operational and maintenance Manuals parts catalog (in the Telugu language) at the time of supply of the equipment to the beneficiaries and awareness should be created to beneficiaries about the machinery. The firm should also supply two copies of such operational and maintenance manuals to the Corporation for official use.
- 15. The manufacturer shall provide TR, insurance for 01 year for all the equipment which are applicable.
- 16. The serial number and any other unique number indicated on the equipment should be communicated along with delivery challan to the end customer point.
- 17. A.P State Agro Industries Development Corporation Limited reserves the right to award offered equipment either in part or full or to empanel on rate contract or follow any other suitable procurement procedure. AP Agros at its sole discretion

- and without assigning any reason thereof, reserves the right to accept / reject any or all bids at any state of the EOI process.
- 18. In case of any dispute or difference arising out of the agreement between the two parties relating to any aspect of the agreement, the parties should attempt to settle the dispute through mutual consent and amicable discussions. If the dispute is not settled through such discussions, the matter shall be referred / settled as per provisions of Arbitration & Conciliation Act.1996.
- 19. It is further to be agreed by both the parties that all differences and disputes if not resolved as above, shall be got remedied through the Court of Law of Vijayawada jurisdiction only.
- 20. EOI can be rejected at any stage of the procurement process, if it comes to knowledge that any Manufacturer(s) is involved in any fraudulent practice or misrepresentation of the facts or tried to influence the selection process or indulged in any corrupt activities in competing with others.
- 21. The approved firm / firms shall enter into an agreement with the Corporation duly incorporating all the above terms and conditions.
- 22. The corrections, if any, must be signed by the applicant before submission itself. In the event of faulty information, the EOI is liable for rejection.
- 23. The Applicant should sign on each and every page of the application and on all the additional documents submitted.

#### E. AFTER SALES SERVICE:

- a. The Manufacturer must provide after sales service to the beneficiaries during the warranty period.
- b. It shall be the responsibility of the Manufacturer to ensure that necessary spare parts are available to the purchaser/customer of machine/equipments during the warranty period and afterward also. For this purpose, the Manufacturer shall keep necessary stock of such fast/slow moving parts with their respective Dealers.
- c. The Manufacturer shall also make arrangements for repair and after sales service required on a continuous basis after the expiry of the warranty period and shall ensure that the repairs/maintenance cost incurred by the purchaser are minimum.

#### F. INSPECTION FOR QUALITY:

The VC & MD, APSAIDCL or their authorized representatives shall have the power:

- (i) To certify any materials or part thereof submitted in EOI for manufacturer.
- (ii) To reject any materials which is not being in accordance with the specifications.
- (iii) To reject the equipment/machinery if having defects portion thereof as it may, in its discretion, think fit, it is satisfied that the same is unsatisfactory.
- (iv) APSAIDCL is having power to inspect if found not satisfactory.
- (v) The VC & MD, APSAIDCL or any officer authorized by VC & MD also has right

to inspect the materials to be dispatched/in Transit/already delivered at anytime and anywhere.

- (vi) The VC & MD, APSAIDCL also has rights to inspect the raw materials used for manufacturing, the process of manufacturing, quality policy fixed, and testing facilities for the product to be supplied by the Manufacturer at the Manufacturer's premises.
- (vii) <u>Cost of Test:</u> The manufacturer is liable to pay the testing charges for any Test done on the products supplied for conformity on quality.

#### G. <u>TERMS OF PAYMENT</u>:

- 1. The APSAIDCL will endeavor to ensure prompt payment within 02 weeks after receipt of the funds from the customer after supply of equipment.
- 2. Payment for the stocks supplied shall be made on receipt of the Company's GST invoices duly certified by the APSAIDCL unit officers based on the proofs of stock receipt by the consignees to be furnished by the company with the tax invoices.
- 3. Name of the service dealer and contact number may be furnished on the invoice of the firm.

I/We have gone through the terms and conditions governing this empanelment and I/we would abide by the terms and conditions laid down in the application for supply of the material.

Note: If there is any changes in terms & condition and adding of additional equipments in future will be intimated through our website only.

PLACE:	
	SIGNATURE OF THE MANUFACTURES
DATE:	WITH SEAL

#### <u>ANNEXURE – I</u>

#### **EOI SCHEDULE**

# CONDITIONS OF ELIGIBILITY FOR MANUFACTURER(S) (Attested copies of following to be enclosed)

1	EOI Reference	:	No: APSAIDCL/GS/2023- 24/005, dt.27-10-2023	Page no
2	Name of the Manufacturing Company with its Regn. No. (copy of the manufacturer license to be enclosed)	:		
3	Status of Company	:		
	i)Registered Company	:		
	ii) Sole proprietorship firm (Name & address of the proprietor)	:		
	iii) Partnership firm (Partnership agreement, letter of consent as authorized by other partners to bid for this tender)	:		
	Private Limited Company (Certificate of incorporation and authorization from CEO, if not represented by CEO)			
4	Registered Address of manufacturing Unit			
5	Particulars of Demand draft enclosed towards cost of tender schedule for the Tender schedules downloaded from website		DD No. date: For Rs.10,000/- Name of the Bank:	
6	Brief Profile of the firm	:		
7	Bank particulars for online transfer of amounts.  a) Bank name & Branch b) Account number c) IFSC Code			
8(a)	Whether the firm is having Valid manufacturing license from the competent authority (copy to be enclosed)	:		
9	Proof of having sufficient No. of technicians with experience (List out details about names of persons / Experience / qualifications)	:		

10	Annual production capacity of the firm (Quantity and	:		
10	value for each equipment to be indicated)			
11	Turnover during last 03 years.	:	a.2020-21: b.2021-22: c.2022-23:	
12	Firm should indicate the no. of districts that can be handled by them. (List of Districts that will be served are to be furnished).	:		
13	Details of dealers' net work and after sales service stations to be provided by firm in the area of operation. (Name & address of each dealer to be listed out)	:		
14	List of equipment available in the manufacturing unit along with technical specifications (to be enclosed)			
15	GST No. /validity (copies to be enclosed)	:		
16	PAN No. (copy to be enclosed)	:		
17	Audited accounts balance sheet for the last 3 years. (attested copies to be enclosed)	:		
18	Income Tax assessment Certificate for the last 03 years (attested copies to be enclosed)	:		
19	Name of contact person with address & Phone no.	:		
20	Details of technical specifications of equipment quoted in price quote.	:		
21	Manuals, parts catalogs, maintenance literature should be enclosed in Telugu language	:		
22	Minimum 02 invoices from the last 03 months for the quoted products	:		
23	Import license no:	:		

#### **Note:**

- 1. All the columns of the EOI forms shall be duly, properly and exhaustively filled in all corrections if any must be signed by the Manufacturer(s) before submission. For filing faulty information, the EOI is liable for rejection. The Manufacturer(s) should sign on each and every page of EOI Schedules and on all the additional documents submitted along with EOI Schedules.
- 2. The Manufacturer(s) can enclose additional information, if any, relevant to the EOI separately
- 3. At the time of verification of EOI schedules, the original documents should be produced for verification.
- 4. Information furnished in the Data Sheet shall also be provided.

SIGNATURE OF MANUFACTURER WITH SEAL

#### ANNEXURE II Technical Schedule

#### **TECHNICAL SPECIFICATIONS OF FOLLOWING EQUIPMENT:**

Specifications to be filled by the Manufacturer with their available specifications of the equipments to be supplied.

- 1. Name of the Manufacturer
- 2. Model
- 3. Specifications
- 4. Testing certificates
  - a. Certificate issued by
  - b. Certificate validity
  - c. Certificate number
- 5. Any other information.

# PRICE QUOTE

## ANNEXURE- III PRICE QUOTE

	Items NoI: Farm Machinery & Equipment	Basic Price	GST	<b>Total Price</b>
1	Land Preparatory Equipments			
2	Secondary Land Preparatory			
	Equipments			
3	Sowing & Planting Equipments			
4	PP Equipments			
5	Harvesting Equipments			
6	Post Harvesting Equipments			
7	Power Tillers / Brush Cutters			
9	Self Propelled Tree Maintenance Platforms			
10	Crop Residue Management Equipments			
11	ISI Marked HDPE Tarpaulins and Multi Layard Cross Laminated			
	Sheets (with size & GSM wise			
	quote)			
12	1 /			
13	Oil Engines & Pump Sets /			
	Electrical Motors			
14	Pheromone Traps + Lures(with item			
	wise quote)			
15	Solar Pest Traps			
16	Yellow Sticky Plates (with item wise quote)			
17	Water Carrying Pipes (PVC/HDPE/Sprinklers)			
18	200 Liters Drum without LID (new HDPE)			
19	100 Liters Drum without LID (new HDPE)			
20	Any other Items required by			
	Agriculture Department			
Iten	1 1			
	ticulture Department Crops			
1	Plastic Crates			
2	Garden Tools			
3	Polishers (for Turmeric)			
4	Boilers (for Turmeric)			
5	Aluminum Ladders (Uni-pole) (for coffee)			
6	Drip irrigation and Sprinklers			
	Aluminum Ladders (Bi-pole) (for			
7	coffee)			
8	Any other Items required by			
	Horticulture Department			

Iten						
	nicipalities & other Go	vernment				
_	eartments/Government					
Ŭ	anizations					
1	Compactors					
2	Vehicle mounted	Sky				
	Lifters/Ladders					
3	Back Hoe Loader					
4	3 wheel/4 wheel Autos					
5	Hydraulic Tippers					
6	Vehicle mounted open	Nala De-				
	silting machines					
7	Vehicle mounted Sewer su	ction cum				
	jetting machines					
8	Sanitary tools, Garden tool	S				
9	Compactor Bins					
10	Canal cleaning machines					
11	Sand cleaning machines					
12	Garbage picking machines					
13	Post hole Diggers					
14	Skid-Steer Loaders					
15		Sweeping				
13	machines	5 weeping				
16	Plastic Bins					
17	Hand Operated Fogging m	achines &				
1 /	Vehicle mounted fogging r					
18	Mist blowing machines (f					
10	of air pollution)	or control				
19	Composting machines					
20	Excavators					
21	Chain mounted Dozer					
22		rinad hrv				
22	•	uired by				
Thom	Municipalities	Pour Food				
	ns No-IV: Equipment f	or roou				
	cessing Industry					
1	Mixer Blenders  Paging Maghinery					
2	Proceeding Machinery					
3	Processing Machinery					
4	Seamers & Cappers	<b>.</b> •				
5	Conveyers / Emulsifiers / A	Agitators /				
	Boilers / Freezers					
6	Pellet making Machinery					
7	Any Other Items required	for Food				
	Processing Industry	<u> </u>				
	nal Husbandry Department &	Sp	ecifications	Basic Price	GST	Total Price
Dair	y 	Single Channa	LECG Complete digital			11100
1	E.C.G for Dogs	portable designed Built-in recharged AC/DC power	I ECG, Complete digital n, Vivid waveform disp argeable Li-ion bat supply, Auto/Manual vole, Lead-off detection	play, tery, work		

		T	1	
		display, Complete digital filtering, resisting		
		baseline drift, AC and EMG interference,		
		Baseline automatically adjustable to optimize printing position, High-resolution		
		thermal printing, Input Circuit - Protection		
		from defibrillation, Lead-Standard 7 leads,		
		Acquisition - Single lead, A/D Resolution -		
		12 bits, Measurement Range - +5mVpp,		
		Time Constraint - 3.2s, Frequency		
		Response - 0.05Hz- 150Hz, Calibration		
		Voltage - 1m V+ 3%, Sensitivity - 2.5, 5,		
		10, 20 (mm/mV), Power Supply -		
		AC:100V- 115V/220V-240V, 50/50Hz -		
		Built-in rechargeable Li- ion battery more		
		than 3 hrs continuous work under battery		
		supply. Display - 192x64 dots LCD. 2		
		years manufacturers warranty.		
		Multi-Purpose Video endoscope-60714		
		PKS/NKS- Sheath-7.9 mm, Working		
		Length - 140 cm, Working Channel- 2.8		
		mm, Deflection up-210 Degrees,		
		Deflection down-100 Degrees, Left/right-		
		120 Degrees.Recommended instruments:		
		for use with 60714 PKS/NKS: 60250 LT -		
		Biopsy Forceps, oval cupped jaws,		
2	Endoscopy for Small Animals	serrated, diameter 2.2 mm, working length		
	Endoscopy for Sman Ammais	200 cm, 60252 LZ Grasping Forceps,		
		serrated, with 1x2 teeth, diameter 2.3 mm,		
		working length 200 cm, 60278 FK Foreign		
		Body Basket, diameter 2.4 mm, length 200		
		cm, 60773 LA Polypectomy Snare,		
		complete, with Handle 60773 H, large,		
		diameter 2.4 mm, length 200 cm. with		
		monitor, laptop and recording facility.		
		2 years manufacturers warranty.		
3	Endo-tracheal Tube with Cuff	Size 3, 3.5, 4 and 4.5"		
)	Disposable			
4	Gloves Obstetrical	22" Length, Latex Full Armed		
	Gioves Costellicai	Monitor should be veterinary specific.		
		Minimum 12" high resolution color TFT		
		Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace		
		Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input		
		Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of		
		Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction		
		Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic		
		Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following		
		Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP,		
_		Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms.Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms.Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms.Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms.Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms.Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms.Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms.Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters.		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2.		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.		
5	Vital Signs Monitor	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful		
5	-	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary		
	Otoscope with light source	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand		
5	-	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view		
	Otoscope with light source	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review		
	Otoscope with light source	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review data with client or for referral.		
	Otoscope with light source	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review data with client or for referral. Easy file/save image documentation		
	Otoscope with light source	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review data with client or for referral. Easy file/save image documentation  Should have 1500cc heavy duty "Coaxial"		
	Otoscope with light source plain	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review data with client or for referral. Easy file/save image documentation  Should have 1500cc heavy duty "Coaxial" absorber, recessed. Preferably molded		
6	Otoscope with light source plain  Small Animal Anesthetic	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review data with client or for referral. Easy file/save image documentation  Should have 1500cc heavy duty "Coaxial" absorber, recessed. Preferably molded Canister Should have Single large		
	Otoscope with light source plain  Small Animal Anesthetic Machine with Isoflurane	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review data with client or for referral. Easy file/save image documentation  Should have 1500cc heavy duty "Coaxial" absorber, recessed. Preferably molded Canister Should have		
6	Otoscope with light source plain  Small Animal Anesthetic	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review data with client or for referral. Easy file/save image documentation  Should have 1500cc heavy duty "Coaxial" absorber, recessed. Preferably molded Canister Should have Single large thumbscrew canister release Should have. 1 to 4 1 pm precision Oxygen flowmeter		
6	Otoscope with light source plain  Small Animal Anesthetic Machine with Isoflurane	Minimum 12" high resolution color TFT LCD display Real time ST Segment, pace maker detection patient info input management system and indication of incorrect manipulation and malfunction analysis. capture dynamic waveforms. Should have following parameters ECG, Respiration, NIBP, SPO2, 2 Temperature and PR/HR. All Probes should be veterinary specific. All sizes of NIBP cuffs for various animals (Enclose catalog with pictures). Spo2 sensor should be able to give correct readings while attached to tongue / tail or perforated areas of animals. Multi lead ECG waveforms display in phase. Large easy to ready values of veterinary parameters. Should be upgradable to IBP and ETCo2. Enclose catalog to ensure that all leads are for veterinary use. Human monitors are not acceptable.  Veterinary video otoscope. UB CAM PRO. UB CAM Pro 2.0TM Videoscope. A useful tool for various applications in veterinary clinics Lightweight, allowing single hand use. Excellent image quality. Live view with still image and video capture. Review data with client or for referral. Easy file/save image documentation  Should have 1500cc heavy duty "Coaxial" absorber, recessed. Preferably molded Canister Should have		

flush valve to prevent accidental activation and Quick connect fresh gas outlet for easy and secure switching between breathing circuits. Should have creservoir bags 0.5L,11, 21, 31, and 51ts.Should Selectatec compatibility manifold for easy and quick installation of any model Vaporizer.Should have Large Quick Lock Inspiration and Expiration domes for easy access and visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve.Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting finishing.Large heavy duty cushioned	
and secure switching between breathing circuits. Should have creservoir bags 0.5L,11, 21, 31, and 51ts.Should Selectatec compatibility manifold for easy and quick installation of any model Vaporizer.Should have Large Quick Lock Inspiration and Expiration domes for easy access and visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve.Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
circuits. Should have creservoir bags 0.5L,11, 21, 31, and 51ts.Should Selectatec compatibility manifold for easy and quick installation of any model Vaporizer.Should have Large Quick Lock Inspiration and Expiration domes for easy access and visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve.Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
0.5L,11, 21, 31, and 51ts.Should Selectatec compatibility manifold for easy and quick installation of any model Vaporizer.Should have Large Quick Lock Inspiration and Expiration domes for easy access and visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve.Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
compatibility manifold for easy and quick installation of any model Vaporizer.Should have Large Quick Lock Inspiration and Expiration domes for easy access and visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve.Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
installation of any model Vaporizer.Should have Large Quick Lock Inspiration and Expiration domes for easy access and visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve.Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
have Large Quick Lock Inspiration and Expiration domes for easy access and visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve.Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
Expiration domes for easy access and visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve. Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible. Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
visibility. Instrument shelf, stainless steel Momentary closed feature incorporated into our pop-off valve. Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible. Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	1
Momentary closed feature incorporated into our pop-off valve.Circuit pressure gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
gauge, easy to read and large Patient circuit pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
pressure alarm audible.Rotating bag mount for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
for ease of visibility and easy access fairy good built in Evacuation connector. high stability frame with good long lasting	
good built in Evacuation connector. high stability frame with good long lasting	
stability frame with good long lasting	
Inishing.Large neavy duty cushioned	
castors, 2 with locks, for easy glide and long life. Easy compatibility for easy	
installation of brain circuit and scavenger	
interface. Oxygen supply hose 9ft, Patient	
circuit with 2 and 3 L bags Drawer module	
atleast 4 drawers with Larger Monitor	
shelf. Scavenger interface, Preset regulator	
Should have all sizes of available	
Veterinary specific masks with diaphragms	
from small feline to large canine.	
Minimum Three year Onsite warranty.	
Should have supplied similar machine to	
some veterinary institution and if required	
demonstration should be given." with AA	
size oxygen cylinders with trolleys with	
Bains circuit rebreathing bags of various	
sizes of 1/2, 1, 2, 3, 5 lits and Sero	
Installation + Bins circuits + Rebreathing Bags of 1/2, 1, 2, 3, 5 liters.	
Sensa Core's ST-200 CL Electrolyte	+
Analyzer is completely automated,	
microprocessor controlled electrolyte	
system that uses current ISE, technology to	
make electrolyte measurements. The ST-	
200CL product measures various	
combinations of sodium, potassium,	
Ionized Calcium, Lithium, pH and	
Chloride in whole blood, serum, plasma,	
and urine. Sensa Core's ST-200CL /	
200Plus / 100B Electrolyte Analyzer	
products are speci_cally designed to meet	
the needs of small to medium-size	
laboratories by Inventing and developing	
8 ST-200 CL Electrolyte the latest technology, Sensa Core's Electrolyte Analyzers improve lab	
Analyzer Productivity, while delivering sample	
results economically. Snap-in electrode	
design, combined with precise control of	
calibrator volumes, ensure economical	
operation and a low cost per sample in our	
Analyzers. Maintenance of Sensa Core's	
Electrolyte Analyzers is limited to the	
replacement of Reagent Pack, Maintenance	
Free Electrodes, Disposable Valve and	
Pump Tube which are just plug and play.	
Depending upon customer requirement ST-	
200CL is Available in two variants in	
terms of Sampling procedure. ST-200CL	
Flip based Analyzer. ST 200CL Slider based Analyzer	
Configuration List: Packing List:	+
Endoscopic Monitor 19 inch - 1, Computer	
Display-1 , LED Cold Light Source-1.	
Display-1 , LED Cold Light Source-1, CCD Camera(700 line) -1, Canon Printer-	1
	1
GCD Camera(700 line) -1, Canon Printer-	
9 Endoscopic Monitor CCD Camera(700 line) -1, Canon Printer-1, Computer-1, Trolley-1, CCD Camera:	

1		HAD CCD, The output		
		pixels,AL:795(H)*598(V), Scanning		
		system PAL:752lines,50field/sce,		
		Synchronization system the synchronous,		
		Horizontal definition ≥700(line), Video		
		output 1.0VP-P.75(ohms), Signal to noise		
		ratio >52dB, Gamma correction 0.45,		
		Electronic shutter 1/50-1/100000 second		
		consecutive, Minimum illumination 0.5lux		
		XF2.,Remote control The camera can lock		
		white balance. LED Cold Light Source:		
		The power supply AC220V,50HZ, LED		
		power 100W 60W for option, Intensity of		
		illumination ≥1400000lux, Output flux		
		1800lm, Color temperature 3000k-7000k,		
		Color rendering index ≥90, The power		
		supply 400-700nm, Noise ≤55dB. Monitor:		
		Display 19" SD, Size ratio 5:4, Distance		
		0.294*0.294mm, Resolution 1280*1024,		
		Chroma 16.7M, Brightness 400, Contrast		
		1400:1, The response time 5ms, Viewing		
		Angle 178°(H)*178°(V), Input signal		
		HDMI/DVI/VGA/CVBS/USB/3G-		
1		SDI/HD-SDI no available, Output signal		
1		CVBS, Power supply AC100-		
		240V50/60HZ, Power 40VA. Option: CCD		
		Camera 900 line/1100 line, Medical		
1		monitor 24 inch, Endoscope ENT mirror,		
		arthroscopy, laparoscopy, etc. Endoscope		
1		Flexible - 1, Laproscope flexible- 1,		
		Otoscope flexible - 1, Gstroscope flexible -		
		1, Opthalmoscope flexible-1, Tracheo -		
		Bronchoscope - 1,		
		ITEMS: Mini reduction forceps serrated -		
		2, Mini periosteal elevator (sizes - 6" & 8")		
		- 1 (In each cetegory), Wire tightner cum		
		twister - 1, Wire passer small - 1, Wire		
		cutter double action - 1, Steinmann pin		
		introducer with SS chuck and key - 1, Self		
		centering Bone holding forceps (Size - 6")		
		- 2, Bone Nibbler straight double action -		
		1, Universal hand drill - 1, Orthopaedic		
		wire (S.S) (Size- 22G, 20G,18G) - 1 (In		
10	Veterinary Orthopedic	ecah category), Steinmann Intramedullary		
10	Pinning and Plating Kit	pins (Size - 2.5mm, 3.0mm, 3.5mm,		
	Timing and Tiating 1th	4.0mm4.5mm, 5.0mm ) - 4 ( In ecah		
		category), Loman bone holding clamp (size		
		- 6") - 2, Liston straight bone cutting		
1		forceps (Size - 6" & 8") - 2 (In ecah		
1		category), Still-Leur double action		
1		rangeurs - 2, Gorden extender - 2, Chisel		
		and Osteotome - 2, Bone curette -2, Bone		
		rasp (size - 8") - 2, Spade - 2, Bone reamer		
		- 2, Intramedullary pin cutter ( Large size) -		
		2, Bone hook -2.		
		Method of Measurement: Oscillometric.		
		Blood Pressure Range: Systolic: 40 -		
		265mmHg, MAP: 27 – 222mmHg,		
		Diastolic: 20 – 200mmHg, Pulse Rate		
		Range: 25 to 300 BPM (Beats Per Minute),		
		Cuff Deflate Rate: Deflation step size		
		varies with heart rate, cuff pressure and		
		cuff volume, Initial Inflation Pressure: 180		
		mmHg (default)		
	Veterinary Blood pressure	Subsequent initial inflation: previous		
11	Monitor Blood pressure	Systolic + 30 mmHg, Transducer		
	IVIOIIIIOI	Accuracy: ±3mmHg between 0 mmHg and		
		300 mmHg, Transducer Calibration:		
		Recommended bi-annually or if a		
		calibration problem is suspected, Operating		
		Conditions: 0°C to 50°C, 15% to 95% non-		
		condensing humidity, Storage Conditions: -		
		20°C to 65°C, 15% to 90% non-		
		condensing humidity, Altitude:		
		Measurement accuracy not affected by		
		altitude, Power: 4 AA alkaline batteries.,		

17.7W Max, Dimensions 6.25" x 5" x 5.25" (1.59 m. x 12.7cm x 13.5cm), Weight 1.31 bx (0.59 kg) with batteries  A SCAN PROBE: Probe frequency: 10  MH. Fixation: Internal LED. Measurement Range, Axial length: 1 Himm to 40mm. ACD: 2 mm-6mm. Lens thickness: 2 mm with the content of the content			A/C Power Adapter - Input: 100-240v ~ 47-63Hz 0.48A Max, Output: 5.9V 3A		
A SCAN PROBE: Probe frequency: 10 MH, Fixation Internal LED, Measurement Range: Axial length: 14mm to 40mm. ACD: 2mm-6mm. Lens thickness: 2mm-7.5mm. Measurement accuracy: 2.0.1 mm. Measurements Techniques: method: Immerion/contact, Mode: Autorinanual. Lens of pers: Aphalick, morrial, dense of the control			17.7W Max, Dimensions: 6.25" x 5" x		
Range: Axial length: 14mm to 40mm.   ACD: 22mm-6mm. Lams hickness: 22mm-7.5mm. Measurment accuracy: 10.1 mm.   Measurment ac			A SCAN PROBE : Probe frequency: 10		
7.5mm. Measurment accuracy: 2-0.1 mm. Measurments Techniques: method: Immerion/contact, Mode: 2 Auto/manual. Lens types: 2 Aphakie, normal, dense cataract, entranct, pseudophakie, silicone oil. (1.0 calculation formulae: SRK-T, SRK-SRK-2, Holladay, Birkhorst, Hoffer-Q, Display: High resolution 8 inch color display with touch screen. Sorrage: 100 patient records, 10 preset user, 220CL configurations. Can more in the state of the configurations. Can more in the configuration in single screen, Printer: 10. Local catalogical in the configuration in single screen, Printer: 10. Local catalogical in the configuration in single screen, Printer: 10. Local catalogical in the configuration in single screen, Printer: 10. Local catalogical in the configuration in single screen, Printer: 10. Local catalogical in the configuration in single screen, Printer: 10. Local catalogical in the configuration in single screen, Printer: 10. Local catalogical in the cata			Range: Axial length: 14mm to 40mm.		
Immerion/contact, Mode : Auto/manual.			7.5mm. Measurment accuracy: ±0.1 mm.		
Ophthalmic Ultrasound Scanner A scan  Ophthalmic Ultrasound Scanner A scan  Ophthalmic IOI calculation formulae: SRK-T, SRK 2, Holladay, Binkhors, Hoffer-Q, Display: High resolution 8 inch color display with touch screen. Storage: 100 patient records, 10 preset user, 2510L configurations, Cam mode: Fast measurement with 101, calculation in single screen. Printer: Fast thermal printer with auto cutter. Lelectrial requirements: 230v AC50Hz  Display Monochrome LCD 5.7° diagonal (120s09mm), Paddle ECG and patient can be ECG GII. Bit standard leads, Thermal array recording, Suitable online USF must be supplied with machine, Rechargeable scaled lead acid battery, Power surply: 100-230 V AC, Warramy 3 years and CMC for next 5 years  14 Absolute Alcohol 2.5 Lts, 99.88 parily; AB Grade Callifornia Mastitis Reagent 1.00000 bromocresol purple pH 7.0 to 7.5, 1.0000 bromocresol purple pH 7.0 to 7.5			Immerion/contact, Mode: Auto/manual.		
Scanner A scan  oil. 10. calculation formulae : SRK-1, SRK 2. Holladay, Binkhorst, Hoffer Q. Display : High resolution 8 inch color display with touch screen. Storage : 100 patient records, 10 preset user, 25100. configurations. Cam mode : Fast measurement with 100. calculation in single screen, Printer: Fast thermal printer with auto curter, Electrial requirements : 2304. AC/50H2  Display: Monochrome LCD 5.7" diagonal (1205/90nm), Paddle ECG and putient cable ECG (Jil & III standard leads, Thermal array recording. Statisble online UPS must be supplied with machine, Rechargeable scaled lead acid battery, Power surply: 100-230 V AC, Warramty 3 years and CMc for next 5 years and CMc for next 9 years 10		Onhthalmic Ultrasound			
Display: High resolution 8 inch color display with touch screen. Storage: 100 patient records, 10 preset user, 2510L configurations. Cam mode : Fast measurement with 10L calculation in single screen, Printer: Fast thermal printer with auto cutter, Electrial requirements: 230v AC/50Hz  Display: Monochrome LCD 5.7° diagnoant (20x00mm), Paddle ECG and patient cable ECG (I.II & III standard leads, Thermal array recording, Suitable online UPS must be supplied with machine, Rechargeable scaled lead acid battery, Power supply: 100-230 V AC, Warranty 3 years and CMC for next 5 years  14 Absolute Alcohol 2.5 Lst. 99.8% purity, AR Grade  15 California Mastitis Reagent 10,000 x in water 10,000 x in	12	1			
patient records, 10 preset user, 2510L configurations, Cam mode : Fast measurement with 101L calculation in single screen, Printer: Fast themal printer with auto cutter, Electrial requirements: 230v AC/50Hz.  Cardiac Defibrillator with Cardiac Defibrillator with ECG  Display: Monochrome LCD 5.7° diagonal (2100-90mm), Paddle ECG and patient cable ECG (J.II & III standard leads, Thermal array recording, Suitable online UPS must be supplied with machine, Rechargeable scaled lead acid battery, Power supply: 100-230 V AC, Warranty 3 years and CMC for next 5 years  14 Absolute Alcohol  15 California Mastitis Reagent  16 Gel Green  10.000X in water  17 Glycerin  18 Iodine Tr. IP  AR grade  19 Petroleum spirit  AR grade (Petroluem ether (40°C - 60°C)  Polyclonal Rabbit Anti Cow-HRPO Conjugate  Polyclonal Rabbit Anti Gow-HRPO Conjugate  Polyclonal Rabbit Anti Gow-HRPO Conjugate  Provides antibody produced in rabbit, diffinity sloated antibody, buffered aqueous solution in 0.01N PBS, PH 7-4 containing 198AS and 0.01% thiomersal. DAKOPATTS P-141 or SIGMA A-7289 / A-5545  Cassefre 5 Kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge, Gross Weight 3.6 Kg, empty Weight 1.6 Kg. Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Sees, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A.B.C and electrically started Fire, B Rating 218, Can Construction: Peop drawa & Co.Q. Mig welded, Valve Construction: Forging & Machining, Internal Couting of Can: Epoxy Powder coating, ExternalCouting of Can: Epoxy Powder coating, Sheet metalthickness 1.60 MM, Helium Leak Decetion Texted Three Years Warranty  23 Gas cylinder with regulator and rubber tube  24 Reverse Osmosis System  A Reverse Osmosis System  A Royerse Osmosis System Or Powder Coating, Starten and Coating of Can: Epoxy Powder Coating, Starten and Edge Coating Can in Epoxy Powder Co			Display: High resolution 8 inch color		
measurement with 10L calculation in single screen, Printer: Fast thermal printer with auto cutter, Electrial requirements: 230v AC/50Hz  Cardiac Defibrillator with Cardiac Defibrillat			patient records, 10 preset user, 25IOL		
with auto cutter, Electrial requirements: 230w ACSOHz			measurement with IOL calculation in		
Display: Monochrome LCD 5.7" diagonal (120x90mm), Paddle ECG and patient cable ECG dnl					
Cardiac Defibrillator with ECG  Cardiac Defibrillator with ECG  State St					
Cardiac Defibrillator with ECG			*		
Rechargeable sealed lead acid battery, Power supply: 100-230 V AC, Warranty 3 years and CMC for next 5 years  2.5 Lis, 99.8% purity, AR Grade  3.7 Sodium lauryl sulphate containing 1:10000 bromocresol purple pH 7.0 to 7.5, 1.5 Periodic pH 7.0 to 7.5, 1.5 Periodic purple pH 7.0 to 7.5, 1.5 Periodic pH 7.0 to 7.5, 1.5 Periodic ph 7.0 to 7.5, 1.5 Periodic ph 7.0 to 7.5 Periodic p	13		Thermal array recording, Suitable online		
years and CMC for next 5 years  2.5 Lis 9,98% purity, AR Grade  2.5 Lis 9,98% purity, AR Grade  3% sodium lauryl sulphate containing 1:10000 bromocresol purple pH 7.0 to 7.5,  16 Gel Green  10,000X in water  17 Glycerin  AR grade  AR grade  AR grade  AR grade  AR grade  Petroleum spirit  Polyclonal Rabbit Anti Cow-HRPO Conjugate  Polyclonal Rabbit Anti Guinea Pig Ig G -HRPO Conjugate  Peroxidase antibody produced in rabbit, affinity isolated antibody, buffered aqueous solution in 0.01N PBS, pH 7.4 containing 198AS and 0.01% thiomersal. DAKOPATTS P-141 or SIGMA A-7289 / A-5545  Casefire 5 Kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge, Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Secs. Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B,C and electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded, Valve Construction: Tested. Three Years Warranty  Gas cylinder with regulator and rubber tube  Gas cylinder with regulator and rubber tube  Reverse Osmosis System  RO Purifier with Hydrostatic Tank enabled		LCG	Rechargeable sealed lead acid battery,		
3% sodium lauryl sulphate containing 1:10000 bromocresol purple pH 7.0 to 7.5.					
11 California Mastitus Reagent 11 Gel Green 11 (10,000 X in water 12	14	Absolute Alcohol	• •		
17 Glycerin AR grade  18 Iodine Tr. IP AR grade  19 Petroleum spirit AR grade, (Petroluem ether (40°C - 60°C)  20 HRPO Conjugate  Polyclonal Rabbit Anti Cow-HRPO Conjugate  Peroxidase antibody produced in rabbit, affinity isolated antibody, buffered aqueous solution in 0.01N PBS, pH 7.4 containing 1%BAS and 0.01% thiomersal. DAKOPATTS P-141 or SIGMA A-7289 / A-5545  Ceasefire 5 Kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge,Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A.B.C and electrically started Fire, B Rating 218, Can Construction: Poep drawn & CO2, Mig welded,Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, Sheet metalthickness: i.60 MM, Helium Leak Detection Tested. Three Years Warranty  23 Gas cylinder with regulator and rubber tube  24 Reverse Osmosis System RO Purifier with Hydrostatic Tank enabled	15	California Mastitis Reagent			
18 Iodine Tr. IP  20 Petroleum spirit  20 Polyclonal Rabbit Anti Cow- HRPO Conjugate  Peroxidase antibody produced in rabbit, affinity isolated antibody, buffered aqueous solution in 0.011 PBS. pH 7.4 containing 1%BAS and 0.01% thiomersal. DAKOPATTS P-141 or SIGMA A-7289 / A-5545  Ceasefire 5 kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge,Gross Weight 3.6 Kg, empty Weight 1.6 kg, Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B.C and electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded, Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  23 Gas cylinder with regulator and rubber tube  24 Reverse Osmosis System  Ro Purifier with Hydrostatic Tank enabled			10,000X in water		
Polyclonal Rabbit Anti Cow- HRPO Conjugate  Polyclonal Rabbit Anti Guinea Pig Ig G -HRPO Conjugate  Peroxidase antibody produced in rabbit, affinity isolated antibody, buffered aqueous solution in 0.01N PBS, pH 7.4 containing 1%BAS and 0.01% thiomersal. DAKOPATTS P-141 or SIGMA A-7289 / A-5545  Ceasefire 5 Kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge,Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Can Height 341MM, Dianeter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B.C and electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded, Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  Gas cylinder with regulator and rubber tube  AR grade, (Petroluem ether (40°C - 60°C) DAKO CAT No P0159  Peroxidase antibody produced in rabbit, affinity isolated antibody, buffered aqueous solution in O.01N PBS, pH 7.4 containing 1%BAS and 0.01% thiomersal. DAKO CAT No P0159  Peroxidase antibody produced in rabbit, affinity isolated antibody, buffered aqueous solution in O.01N PBS, pH 7.4 containing 1%BAS and 0.01% thiomersal. DAKO CAT No P0159  Peroxidase antibody produced in rabbit, affinity isolated antibody produced in rabbit, affinity isolated antibody produced in rabbit, affinity isolated antibody purisonated antibody produced in rabbit, affinity isolated antibody produced antibody produced in rabbit, affinity isolated antibody produced in rabbit, affinity	-	•			
Polyclonal Rabbit Anti Cow - HRPO Conjugate  Polyclonal Rabbit Anti affinity isolated antibody produced in rabbit, affinity isolated antibody, buffered aqueous solution in 0.01N PBS, pH 7.4 containing 1%BAS and 0.01% thiomersal. DAKOPATTS P-141 or SIGMA A-7289 / A-5545  Ceasefire 5 Kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge, Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B,C and electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded, Valve Construction: Deep drawn & CO2, Mig welded, Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  Gas cylinder with regulator and rubber tube  Gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, 1SI and ISO standards with 5 years manufacturing warrenty  Reverse Osmosis System  RO Purifier with Hydrostatic Tank enabled			-		
Polyclonal Rabbit Anti affinity isolated antibody produced in rabbit, affinity isolated antibody, buffered aqueous solution in 0.01N PBS, pH 7.4 containing 1%BAS and 0.01% thiomersal. DAKOPATTS P-141 or SIGMA A-7289 / A-5545  Ceasefire 5 Kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge, Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B,C and electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded, Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  Gas cylinder with regulator and rubber tube  Gas cylinder made up of carbon steel along with compatible regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  Reverse Osmosis System  RO Purifier with Hydrostatic Tank enabled	19	•	AR grade, (Petroluem ether (40°C - 60°C)		
Polyclonal Rabbit Anti Guinea Pig Ig G -HRPO Conjugate  21 Guinea Pig Ig G -HRPO Conjugate  Rabbit Anti Guinea Pig Ig G -HRPO Conjugate  Polyclonal Rabbit Anti Guinea Pig Ig G -HRPO Conjugate  Rabbit Anti Guinea Pig Ig G -HRPO Conjugate  Polyclonal Rabbit Anti Guinea Pig Ig G -HRPO Controllate  Polyclonal Rabbit Anti Guinea Pig Ig G -HRPO Controllate  Polyclonal Rabbit Anti Guinea Pig Ig G -HRPO Controllate  Polyclonal	20				
Conjugate    Solution in 0.01N PBS, pH 7.4 containing 1%BAS and 0.01% thiomersal. DAKOPATTS P-141 or SIGMA A-7289 / A-5545		Polyclonal Rabbit Anti	affinity isolated antibody, buffered aqueous		
Conjugate  DAKOPATTS P-141 or SIGMA A-7289 / A-5545  Ceasefire 5 Kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge,Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B,C and electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded,Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  Gas cylinder with regulator and rubber tube  To kg LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  RO Purifier with Hydrostatic Tank enabled	21	Guinea Pig Ig G -HRPO			
Ceasefire 5 Kg Fire Extinguisher Clean Agent FE 36, Zero ODP, Stored Pressure Type, Pressure Gauge,Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B,C and electrically started Fire, B Rating 218, Can Construction : Deep drawn & CO2, Mig welded,Valve Construction : Forging & Machining, Internal Coating of Can : Epoxy Powder coating, ExternalCoating of Can : Epoxy Polyster Powder coating, Sheet metalthickness :1.60 MM, Helium Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS , ISI and ISO standards with 5 years manufacturing warrenty  24 Reverse Osmosis System  RO Purifier with Hydrostatic Tank enabled		Conjugate	DAKOPATTS P-141 or SIGMA A-7289 /		
Type, Pressure Gauge, Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Can Height 341MM, Diameter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B,C and electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded, Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  Ro Purifier with Hydrostatic Tank enabled			Ceasefire 5 Kg Fire Extinguisher Clean		
341MM, Diameter 108 MM, Discharge Time minimum 6 Secs, Controllable discharge mechanism, Range minimum 2 Meters, applicable on Class A,B,C and electrically started Fire, B Rating 218, Can Construction : Deep drawn & CO2, Mig welded, Valve Construction : Forging & Machining, Internal Coating of Can : Epoxy Powder coating, ExternalCoating of Can : Epoxy Polyster Powder coating, Sheet metalthickness :1.60 MM, Helium Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS , ISI and ISO standards with 5 years manufacturing warrenty  24 Reverse Osmosis System RO Purifier with Hydrostatic Tank enabled			Type, Pressure Gauge, Gross Weight 3.6		
discharge mechanism, Range minimum 2 Meters, applicable on Class A,B,C and electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded,Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  24 Reverse Osmosis System  RO Purifier with Hydrostatic Tank enabled			341MM, Diameter 108 MM, Discharge		
22 Fire extinguisher  electrically started Fire, B Rating 218, Can Construction: Deep drawn & CO2, Mig welded, Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  24 Reverse Osmosis System  RO Purifier with Hydrostatic Tank enabled			discharge mechanism, Range minimum 2		
Construction: Deep drawn & CO2, Mig welded, Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  Reverse Osmosis System RO Purifier with Hydrostatic Tank enabled	22	Fire extinguisher			
Machining, Internal Coating of Can: Epoxy Powder coating, ExternalCoating of Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  Reverse Osmosis System  RO Purifier with Hydrostatic Tank enabled					
Can: Epoxy Polyster Powder coating, Sheet metalthickness: 1.60 MM, Helium Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  24 Reverse Osmosis System RO Purifier with Hydrostatic Tank enabled			Machining, Internal Coating of Can:		
Leak Detection Tested. Three Years Warranty  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  Reverse Osmosis System RO Purifier with Hydrostatic Tank enabled			Can: Epoxy Polyster Powder coating,		
Gas cylinder with regulator and rubber tube  5 kgs LPG gas cylinder made up of carbon steel along with compatble regulator, 3 mts 3 layer gas pipr should meet BIS, ISI and ISO standards with 5 years manufacturing warrenty  Reverse Osmosis System RO Purifier with Hydrostatic Tank enabled			Leak Detection Tested. Three Years		
23 and rubber tube regulator and rubber tube regulator, 3 mts 3 layer gas pipr should meet BIS , ISI and ISO standards with 5 years manufacturing warrenty  24 Reverse Osmosis System RO Purifier with Hydrostatic Tank enabled			5 kgs LPG gas cylinder made up of		
years manufacturing warrenty  Reverse Osmosis System RO Purifier with Hydrostatic Tank enabled	23		regulator, 3 mts 3 layer gas pipr should		
		and rubber tube			
(B10)   WILL KU+U V+UF+1D3 CORORET,SURADE	24	Reverse Osmosis System (Big)	RO Purifier with Hydrostatic Tank enabled with RO+UV+UF+TDS Contoller;Suitable		

		,	ı	Ī	
		for Purification of Brackish / Tap			
		Water;Storage Capacity 9 L;Purification			
		Production Rate 15 L/hr;Input Power			
		Supply Single Phase 220 ± 10 V AC, 50 Hz,WQA, NSF and ISI certifi			
		Production flow rate rate 5litres per			
		hour,particles -no particles with size more			
	Marin O. I.	than 0.22micrometres, bacteria less than			
25	Milli-Q ultrapure type I water	0.01 CFU per millilitre, endotoxins-less han			
	purification system	0.01EU/ml,TOC-less than 2 PPB			
		dimensions: H X W X D 498 X315 X			
		380mm, 5 years warranty			
		For quantitave measurement of somatic			
		cells in fresh milk samples of bovines in			
26	Hand held smart strip based	sub clinical and clinical mastitis with a			
26	somatic cell counter	hand held portble blue tooth connected,			
		smart phone integrated. Should have			
		measuring range of100-1200cells /micr litre.			
		Sub-Cell GT Electrophoresis Cell should			
		have greatest choice of gel lengths, sample			
		combs, and separation modes, ideal for			
27	Curls and CT and	Southern and northern blotting protocols.			
27	Sub-cell GT cell	Up to 30 samples can be resolved over a			
		distance of 25 cm. Using four rows of			
		combs, the cell will run up to 120			
		analytical samples.			
		Upright bright field, digital portable			
		microscope with integrated tablet display			
		(no eyepiece), application and research grade optics, Detachable tablet slot			
		Robust opto-mechanical system for field			
		use without alignment issues			
		Dimensions: 18cm (W) x 19.5cm (L) x			
		18cm (H) excluding display screen			
		Weight: <3 kgs			
		True View technology for capture of 100%			
		circular field of view through the tablet			
		camera, Quadruple outward facing			
		nosepiece			
		Four high contrast plan achromate			
		objective lenses – 4x, 10x, 40x, 100x oil			
		immersion, Internal magnification 10X with the following captured FoV: 5 mm			
		with 4x objective, 2 mm with 10x			
		objective, 0.5 mm with 40x objective and			
		0.2 mm with 100x objective			
		1.25 NA condenser; 1 watt LED			
		illumination with intensity control			
		Rackless X-Y stage			
		Coaxial coarse and fine focus knobs on			
28	Tab Digital Microscope	both sides			
		Inbuilt rechargeable lithium ion battery			
		with 15 hour backup, DC adapter for charging, Provision for backup power			
		supply to tablet from battery			
		Tablet with maximum camera resolution of			
		atleast 3264x2448 pixels and 9.7" display			
		with 2048 x 1536 pixels resolution; 2/3GB			
		RAM, 32 GB ROM			
		Full HD video capture at 1920x1080 pixels			
		Pre-installed application with following			
		features:			
		• Data management • Image capturing •			
		Video recording • Exposure, brightness,			
		saturation, temperature and contrast control     Micrometry – linear and circular			
		measurements in microns			
		• Free hand marking and pointer for			
		demonstration • Profile creation for			
		separate users			
		Variable resolution of upto 8 MP			
		Wireless HDMI dongle for lag-free real			
		time casting to projector or LCD screen			
		1 year warranty, Padded carry bag with			
		compartments Accessory kit comprising of			

	Ι	lint-free cleaning cloth, dust cover and		
		immersion oil.		
29	UPS with 1KV Battery backup	Equipped with a maintenance free sealed Lead Acid battery with suspended electrolyte having a typical recharge time of 15 hours. The output power capacity of the UPS is 600 Watts/ 1000VA and nominal output voltage is 230V.		
30	Refrigerator	Double door Refrigerator - with Auto defrost, energy efficient, less noise & More durable inverter compressor with 10 years warranty, 310 Ltr capacity with adjustable rustproof shelves shelf with toughened glass to withsatand the weight of heviest vessels, 2 star rating, Product along with double booster 2KV stabilizer		
31	Conical flasks-100 ml with screw cap	100 ml, High resistance to chemicals, Heat, screw cap made of polypropylene, neck specification GL25, 20/case		
32	Conical flasks-1000 ml with screw cap	1000 ml, High resistance to chemicals, Heat, screw cap made of polypropylene, neck specification GL45, 10/case		
33	Conical flasks-2000 ml with screw cap	2000 ml, High resistance to chemicals, Heat, screw cap made of polypropylene, neck specification GL45, 10/case		
34	Conical flasks-250 ml with screw cap	250 ml, High resistance to chemicals, Heat, screw cap made of polypropylene, neck specification GL45, 20/case		
35	Conical flasks-50 ml	50 ml, Complies with IS 1381(Part I),ISO / DIN 1773, High resistance to chemicals, Heat, 51X90mm, 100/case		
36	Micrometer slides	Stage (ESM-11) and ocular (EOM-11) Micrometer slides, unit		
37	Bio chemical kits for fully automatic biochemical analyzer for serum albumin	For estimation of serum albumin, kinetic / end point estimation compatable to fully automatic analyzer (idexx) ( 50 test kit)		
38	Biochemical kit for fully automatic biochemical analyzer for Alkaline Phosphatase	For estimation of serum Alkaline Phophotase, kinetic / end point estimation compatable to fully automatic analyzer (idexx) (50 test kit)		
39	Biochemical kit for for fully automatic biochemical analyzer for serum ALT	For estimation of serum ALT , kinetic / end point estimation compatable to fully automatic analyzer (idexx) ( 50 test kit)		
40	Biochemical kit for fully automatic biochemical analyzer for serum AST	For estimation of serum AST, kinetic / end point estimation compatable to fully automatic analyzer (idexx) ( 50 test kit)		
41	Biochemical kit for serum Magnesium - For fully automatic analyzer (idexx)	For estimation of serum Inorganic magnisium, kinetic / end point estimation compatable to fully automatic analyzer(idexx) (50 test kit)		
42	Biochemical kit for serum Potassium -For fully automatic analyzer (idexx)	For estimation of serum Inorganic magnisium, kinetic / end point estimation compatable to fully automatic analyzer(idexx) (50 test kit)		
43	Biochemical kit for fully automatic analyzer for serum Total Proteins	For estimation of serum total Proteins , kinetic / end point estimation compatable to fully automatic analyzer (idexx) ( 50 test kit)		
44	Biochemical kit for fully automatic analyzer serum Urea Nitrogen	For estimation of serum Urea Nitrogen , kinetic / end point estimation compatable to fully automatic analyzer (idexx) ( 50 test kit)		
45	Blood - TUBES QBCW/STRIPE (IDEXX)	Tubes for Auto Read Idexx hematology analyzer		
46	Controls for Semi Automatic Hematology Analyzer	Quality Controls for all the parameters of Semi Automatic Haematology Analyzers (Mindray)		
47	ELISA Kit- Malignant Catarrhal fever Antigen	8/16 well strip format.Unit: 12 or 6 strips to fit into 96 well plate.Should have		

	detection kit	specificity and sensitivity more then 95% +/- 2% variation.		
48	ELISA Kit-Malignant Catarrhal fever Antibody detection kit	96 well plate format. Should have specificity and sensitivity more then 95% +/- 2% variation		
49	FAMACHA Cards	Plastic card with 5 high-resolution photos, Numerically designates each stage of anaemia		
50	Hand Disinfectant Gel	62% denatured Ethanol, 3.3% 2-Propanol, Gel with Moisturiser		
51	IDEXX E-Z prep Pipetter	for veterinary use only, for filling IDEXX vet tubes.		
52	IDEXX vet tubes	for Veterinary use only, each kit contains 10 venous blood tubes,		
53	IDEXX VetTrol Control	VetTrol Control is a lyophilized, bovine- based control fluid, specially formulated for use on IDEXX VetTest, VetLyte and Catalyst analyzers.		
54	Kits for Semi Automatic Biochemical analyzer	For estimation of Total Protien, AST, ALT, Bilurubin, createnine, BUN, albumin, calcium, Phosphorus, Mg comaptable for Semi-Automaitc Biohemical Analyzers (Mindray/Vkemnext)		
55	Kits-Blood - BOVINE Hematology sample prep kit for Idexx analyzer	kit for AutoRead Idexx hematology analyzer, for 30 tests		
56	Mac master egg counting Chamber (glass)	Evaluate Egg per gram in a given feacal / dung specimen.		
57	Microscopic slide tray	Holds upto 20 standard microscopic slides at an angle, 50/box		
58	Paraffin -wax	58-60 degree centigrade-Mercks Company only		
59	Poly propylene vials	2 ml		
60	Sample cups with cap for clinical chemistry analyzer	Box with serum vial stand (100 samples)		
61	Specimen Container 250ml	Wide mouth, Medical grade, 250ml, PP made		
62	Strip cup for mastitis test	Plastic strip cup with black plastic screen for easy ID of any flakes or clots of abnormal milk. Approx. 4 3/4 inches tall x 6 1/4 O.D. Washes easily with warm water or throw it in your wash sink and wash it with the pipeline.		
63	U-V Lamps with cabinets	4feet length,30w tube & Accessories		
64	Vacutainer with K2 EDTA	Blood collection tubes 2 ml(Double cap)		
65	Wall mounted SOP display boards (pads)	SS make Aluminium Frame, 1.5x2 Feet		
66	Whatman filter paper	Cellulose filter paper Grade41, 18.5 C.M		
67	Whatman filter paper	Cellulose filter paper Grade 42, 18.5 C.M		
68	Whatman filter paper no 40	Cellulose filter paper Grade 40, 18.5 C.M  A lateral flow immunochromatographic		
69	Brucella anti body rapid detection test kit	assay for the qualitative detection of brucella specific antibodies in whole blood/ sera/ plasma.		
70	Ammonium sulphate solution	AR grade 5% defibrinated sheep blood, for fastidious		
71	Blood Agar readymade plates	organisms, to demonstrate hemolytic ability of organisms. At least 3month shelf life Sterile, autoclavable after use. Pk/6		
72	Liquor ammonia	AR		
73	Lugols Iodine	AR Grade		
74	Magnesium sulphate	Magnesium sulphate hepta hydrate		
75	RG stain	Romanowsky-Giemsa stain, AR grade		
76	Sodium Nitrite	AR grade		

77	Uristix	Dip and read urine analysis, 20 test kit		
78	Centrifuge tubes	Glass with gradation for 0.2 ml, 15 ml capacity		
79	Watch glass	100 mm diameter, glass, <b>10/case</b>		
80	Immersion Oil-Type	Immersion specific for / nikon/microscope/-TypeF, 30 ml, single		
81	Leak Proof Containers	Made up of Plastic, leak proof		
82	Ammonium Hydroxide	AR Grade, strong		
83	Sodium/ Potassium Hydroxide flakes	AR grade		
84	Microscope Slides	The glass slides should be made from optically clear flat glass, uniform thickness of 1.35 mm, 75 mm long and 25 mm wide. The slides have ground edges and lint free packing.		
85	Microscopic slides-Frosted	white colored frosted one end one side (76x26x0.95mm),50/box		
86	Brush Cutters			
87	Tractor Mounted Single Row forage Harvester cum Chaffer			
88	Vermicompost Unit			
89	Mawa Making unit			
90	Ghee Making unit			
91	Butter chilling unit			
92	Urine Distillery Unit			
93	Cow dung log machine			
94	Panchagavyam unit			
95	Jeevamrutham Unit			
96	Agarbathi Making unit			
97	Biochemical Analyzer			
98	X-Ray Unit Digital			
99	Large Animal Trolley cum Operation table			
100	Ultraviolet lights			
101	Movable Trolley			
102	LCD Projector with screen			
103	White Board with stand			
104	Digital X-Ray Machine			
105	Endoscopy for small animals			
106	Large animal operation table with hydraulic system			
107	Boyles apparatus			
108	Movable Large Animal Surgical Table			
109	Morbros make General surgery semi electric OT Table			
110	Large Animal multiple Use Trolley - For Transportation and surgery - custom made Sizes: length 7/8 feet , width: 5/6 feet and height 2 feet with or without heavy duty wheels			

		ı	i	1	
111	PZ make AD X model				
111	500MAX Ray Machine with				
110	DR System				
112	Largngo Scope				
113	Spay hook				
114	Woods Lamp				
115	Eye Speculum				
116	Vital Sign Monitor				
	Inhalation anesthetic Machine				
117	with automatic ventilation				
	support along with isoflurane				
	vaporizer				
	United Surgical Model make				
118	double dome Surgical operating LED light Model				
	80D				
119	ECG Machine				
120	Doppler BP Monitor				
120					
	Vet Endoscopy				
122	Infrared Thermometer				
123	LED pocket Otoscope  Binocular Indirect				
124	Binocular Indirect Ophthalmoscopes				
125	Endotracheal tube size 16				
126	Endotracheal tube size 18				
127	Endotracheal tube size 20				
128	Endotracheal tube size 22				
129	Metal Detector				
	Autoclave with 4 Dressing				
130	Drums, 2 drums can be fitted				
	with autoclave				
131	Backhaus towel clamps				
132	Large animal anesthetic				
133	machine wireless oscillating ortho saw				
134	Rubber mats				
135	Wire Tensioner				
136	Hammer				
137	LCP PLATE - 2.7mm - 6H LCP PLATE - 2.7mm - 8H				
138 139	LCP PLATE - 2.7mm - 8H LCP PLATE - 2.7mm - 10H				
	LCP SCREW - 2.7mm -				
140	10mm				
141	LCP SCREW - 2.7mm -				
141	12mm				
142	LCP SCREW - 2.7mm - 14mm				
1.42	LCP SCREW - 2.7mm -				
143	16mm				
144	LCP SCREW - 2.7mm -				
	18mm LCP SCREW - 2.7mm -				
145	20mm				
				_	

146	LCP PLATE - 3.5mm - 8H			
147	LCP PLATE - 3.5mm - 10H			
148	LCP PLATE - 3.5mm - 12H			
149	LCP SCREW - 3.5mm - 14mm			
150	LCP SCREW - 3.5mm - 16mm			
151	LCP SCREW - 3.5mm - 18mm			
152	LCP SCREW - 3.5mm - 20mm			
153	LCP SCREW - 3.5mm - 22mm			
154	LCP SCREW - 3.5mm - 24mm			
155	LCP SCREW - 3.5mm - 26mm			
156	LCP SCREW - 3.5mm - 28mm			
157	LCP SCREW - 3.5mm - 30mm			
158	Nebulizer			
159	X-ray-illuminator			
160	Travis			
161	Auto clave			
162	Surgical bins			
163	Autoclave			
164	Thermo cautery			
165	Large animal surgical Kit			
166	Small animal surgical kit			
167	Pulse Oximeter			
168	Operation table for small ruminants			
169	Hydraulic operation table for large animals			
170	Surgical Oscillating saw			
171	Suturing material Air Conditioner in Operation			
172	theatre			
173	Inhalation Anesthetics Machine			
174	Surgical light Head			
175	Vital signs Monitor			
176	Otoscope			
177	Electronic Stethoscope			
178	ECG machine			
179	Microscope with Monitor			
180	Vein finder			
181	Gastro scope			
182	Vet scope			
183	Electric thawing Units			
L			l	

184	Anesthetics		
185	Drapes		
186	Surgical needles		
187	Mouth Gags		
188	Trocar and cannula( large & small)		
189	Rumen Puncture Needle		
190	Obstetrical Hooks		
191	Obstetrical Lubricants		
192	Disposable Plastic polygraphs for Surgeries		
193	Electrical fans		
194	LED tube lights		
195	LPG gas and stove with regulator		
196	Electrical shaver		
197	Manual Shavers		
198	Towel clips		
199	liquid soap		
200	PH papers		
201	Glass slides		
202	Fore Head Thermometers		
203	Case sheets		
204	Registers		
205	Infrared Bulb		
206	Ketamine		
207	Table for ultra sound machine		
208	Lead Aprons		
209	Lead Glues		
210	Chemicals for Developer, Fixer Rinser		
211	Tanks for holding chemicals for development of film		
212	Safe Light		
213	Normal Tube Light		
214	Films (8X10, 10,12, 12X15)		
215	Clips		
216	Existing fan for dark room		
217	Saline stands		
218	Gaseous anesthesia with isoflurane vaporizer		
219	DIGITAL X-RAY UNIT		
220	Orthopedic kit		
221	Ultrasound latest version		
222	Autoclave tubular		
223	Surgical Suction machine for large animals		
224	Large Animal Sling(lifting		

	system for recumbent /downer animal		
225	Surgical equipments (arteries, tissues, scissors, B.P.handles, Rumenotomy set, Retractors, suture material, stools revolving et., for Large animal & Small animal surgeries)		
226	Veterinary ECG machine		
227	Heavy duty trolley (1-ton capacity)for transportation of recumbent animal from ambulance to the ward		
228	Thygesen embryortome set with wire saw		
229	Hydraulic Surgical table for large animal (1 ton capacity)		
230	Godrej Steel Almirah		
231	ECG		
232	Boyles Apparatus		
233	Electric Thermo Cautery		
234	Magnetic Loup		
235	Orthopedic Equipment		
236	AC		
237	Saline stands		
238	Medicine Storage Cabinet (Steel Shelve)		
239	Saline Stand		
240	Small animal Operation table		
241	Iron Racks		
242	Electrical Shavers		
243	Thermometers		
244	UV Lamp		
245	Small animal OT Table		
246	Shadow less light for surgery (Operations)		
247	Digital X-ray machine		
248	Portable Digital X Ray Machine		
249	Portable digital X-Ray Machine		
250	Needle Holders		

#### **Note:**

- 1. The rates may be quoted for all the above equipment individually.
- 2. The basic rates quoted <u>shall be inclusive</u> of all Taxes / Duties / CESS / OCTROI / Loading/ unloading etc. for delivery at end customer point. GST shall be shown separately
- 3. The rates and units shall <u>not be over written</u>. The rates and units shall always be both in figures and words.
- 4. TR/PR (Insurance for 1 year) should in the separately

Pla	ace:
Da	ıte

SIGNATURE OF MANUFACTURER WITH SEAL

#### **ANNEXURE-IV**

## DECLARATION ON Rs.100/- NON JUDICIAL STAMP PAPER (TO BE NOTARISED)

- 1. I/we have read and understood the Terms and Conditions of EOI Schedule relevant to "EOI notice" dated:27-10-2023 and I/we have submitted the Annexures in accordance with the Terms and Conditions of above EOI Schedule.
- 2. I/we shall not sell the products quoted through this EOI schedule, at a lower price either to Government / Private Parties/farmers in the State of Andhra Pradesh by way of giving any additional trade discount or incentives. If any such incident is noticed, the A.P.S.A.I.D.C. Ltd. has the right to restrict all payments to such a lower rate apart from initiating penal action.
- 3. The information furnished in the Annexure-1 is true and factual and I clearly understand that our EOI schedule is liable for rejection, if any information furnished is found not true at any point of time.
- 4. The product/s offered by us is not copied or duplicated from any other product design. In case the Corporation authorities find at any time our products are an imitation or duplicated, we are bound for any legal action to be taken on us including criminal prosecution and blacklisting of our firm.
- 5. I/We declare that I/We do not violate any patent/trade mark rights of any other manufacturer.

PLACE:	
	SIGNATURE OF THE MANUFACTURER
DATE:	WITH SEAL